

Σ-Ahr PWM Controller

The charge controller is the beating heart of any solar energy system. The desire for perfection at TSS has resulted in the most solid and most efficient pulse width modulation (PWM) charge controller for stand-alone solar energy systems. It is designed to have exceptional performance and last longer especially in the most harsh environments.



Efficiency 99.75%

This reduces your overall system cost.

Ultimate reliability

The multi array input eliminates a single all-or-nothing connection. Fully solid state. No mechanical relays. No cooling fans.

Remote monitoring

Controller is equipped with an industry standard Modbus TCP/IP interface for easy and reliable remote monitoring.

Datalogging

8 key system parameters are daily logged and stored for maximum 60 days.

Triple redundancy

The analogue fall back mode kicks in should the processor ever fail. More than one voltage and temperature measurement can be incorporated for maximum reliability. Two completely independent voltage measurements are monitored against high and low voltage.

Small and large systems

A modular design allows for expansion when larger systems are required.

In-field diagnostics

With pushbuttons the main function of the controller can be tested in the field.

Σ-Ahr PWM Controller

Electrical specifications	Σ-Ahr PWM Controller 24V		Σ-Ahr PWM Controller 48V	
Nominal system voltage	24 Vdc		48 Vdc	
Independent solar array inputs	3		3	
Nominal total array input current	134 Adc		134 Adc	
Maximum array input current	3x 50A		3x 50A	
Max. array input voltage	90 Vdc		90 Vdc	
Max. continuous battery current	134 Adc		134 Adc	
Max. battery input voltage	65 Vdc		65 Vdc	
Independent load outputs	2		2	
Nominal output current to load	2 x 45 Adc		2 x 45 Adc	
Maximum output current to load	2 x 60 Adc (1 minute)		2 x 60 Adc (1 minute)	
Peak output current to load	2 x 90 Adc (10 seconds)		2 x 90 Adc (10 seconds)	
Operating efficiency solar input	99.75 %		99.75 %	
Typical settings (24Vdc)	Lead Acid	Nicd (19 cells)	Lead Acid	Nicd (38 cells)
Load disconnect / high system voltage (alarm)	30.5 Vdc	31.5 Vdc	61.0 Vdc	63.0 Vdc
Load re-connect high voltage	28.8* Vdc	28.5 Vdc	57.6* Vdc	57.0 Vdc
Boost @ 25 °C level	28.8* Vdc	N.A.	57.6* Vdc	N.A.
Float @ 25 °C level	28.2 Vdc	28.5 Vdc	56.4 Vdc	57.0 Vdc
Low battery voltage (alarm, non-essential load disconnect)	23.6 Vdc	23.0 Vdc	47.2 Vdc	46.0 Vdc
Non-essential load re-connect voltage	25.0 Vdc	25.0 Vdc	50.0 Vdc	50.0 Vdc
Load disconnect low voltage (alarm, essential load disconnect)	23.0 Vdc	21.85 Vdc	46.0 Vdc	43.7 Vdc
Essential load re-connect voltage	24.5 Vdc	24.5 Vdc	49.0 Vdc	49.0 Vdc
Temperature compensation	-3mV / °C / cell	N.A.	-3mV / °C / cell	N.A.
* Boost and float voltage for Lead Acid are temperature dependent				
Monitoring and logging				
Key system parameters logged	8			
Logging interval	Daily			
Maximum storage time	60 days			
Communication (external)	Modbus TCP/IP (slave)			
General specifications				
Operating temperature	-20 °C to +85 °C			
Storage temperature	-30 °C to +85 °C			
Humidity	100% non-condensing			
Mounting	Indoor			
Dimensions (H x W X D)	16.0 x 8.0 x 14.6 cm			
Unit weight	0.98 kg			
Communication (between Σ-Ahr units)	RS-485			
Analogue input	2x 100mV shunt			
Digital output	3x open drain			
Approvals	CE			
Standards	IEC 61000-6-2 IEC 61000-6-4 IEC 60950-1			