

Solar Energy for Motor Operated Loads

A motor operated load such as a wellhead control panel (WHCP) is the main part of a safety system on an oil production site. The main function of a WHCP is to ensure controlled opening and closing of valves during emergency situations. These panels which are remotely located in extreme environmental conditions operate a few hours every day, which makes the energy requirement low while the power requirement is high. Standard available charge controllers are not designed to supply such a high power demand. TSS' specially designed industrial grade charge controllers meet such a high power requirement with or without metering.

TSS Unique Features

- Pre-designed solution, thus no engineering cost
- Lowest energy consumption - saving costs
- Robust design for use in harsh environmental conditions and high load demands.
- Can also be customized for hazardous operating conditions
- Voltage/Temperature sensor incorporated to ensure longer battery lifetime
- Temperature compensated battery charging
- No need for additional output relay, thus increasing reliability
- Ease of operation and testing with user friendly test buttons
- TSS Solar Energy System can be built inside client's control panel.



Choice of TSS Charge Controllers

Typical specifications	SolAhr PWM Controller	MRCC PWM Controller
Nominal voltage	24 Vdc	24 Vdc
Solar array inputs	1	1
Max. continuous array input current	75 Adc	31.5 Adc
Max. array input voltage	80 Vdc	75 Vdc
Max. battery input voltage	60 Vdc	40 Vdc
Max. load output current	80 Adc (cont.) 100 Adc (1 minute)	24 Adc (cont.) 40 Adc (1 minute)
Peak load output current	500 Adc (1 second)	250 Adc (1 second)
Max. terminal connector size	35 mm ²	16 mm ²
Display Availability	✓	✗
Passive Battery Voltage Transducer (4-20mA)	✓	✗
Volt/Temp Sensor	✓	✓
Low Voltage Alarm	✓	✓
Test Switch/Button	✓	✓
High Voltage/Load Disconnect Alarm	✓	✓
Earth Fault Alarm (>100mA)	✓	✗
Battery type	VRLA or NiCd	VRLA

General specifications		
Operating temperature	-20° C to +85° C	-10° C to +85° C
Storage temperature	-30° C to +85° C	-30° C to +85° C
Humidity	100% non-condensing	100% non-condensing
Mounting	Indoor	Indoor
Dimensions (H x W X D)	16.0 x 21.0 x 5.5 cm	17.3 x 10.2 x 6.0 cm
Unit weight	0.55 kg	0.40 kg

TSS Example System Sizing

PV Modules	Insolation/day			
	3 kWh/m ² /day	3.75 kWh/m ² /day	4.5 kWh/m ² /day	5.25 kWh/m ² /day
	24 Vdc	24 Vdc	24 Vdc	24 Vdc
1	30 Ah/day	37 Ah/day	50 Ah/day	53 Ah/day
2	60 Ah/day	74 Ah/day	100 Ah/day	106 Ah/day
3	90 Ah/day	111 Ah/day	150 Ah/day	159 Ah/day

*Load per day based on installed modules and location specific insolation

Based on the specific load requirement and space availability, the type and number of PV modules and batteries can be customized. Additionally, a single line diagram and IOM manual would be provided for hassle free self-installation on the site.

This datasheet is not legally binding. Actual specifications and / or product features may vary. TSS4U BV reserves the right to make changes to specifications without notice